

ACHBEST COMPANY LTD., YANTAI

RM. 1004 TRIUMPH CENTER, NO. 53 NANSHAN ROAD, YANTAI, CHINA

产品质量证明

CERTIFICATE OF QUALITY

品名

Commodity: E. GALV. WIRE ROPES

结构

Construction 6X7+FC

捻向

Lay Direction RHOL

涂油方式

Lubrication WITHOUT OIL

总数量

Total Quantity 1000M/ REEL

生产标准

Standard : DIN 3055

钢丝绳破断拉力

The least Breaking Strength $\geq 2.56\text{KN}$

公称直径

Nominal Dia 2.0MM

钢丝直径

Wire Dia 0.21MM

公称强度

Nominal Strength $\geq 1770\text{MPA}$

判定：根据以上检验结果，符合产品标准 DIN 3055 要求，准予出厂。

Conclusion: According to the above test result, they accord with the demands of products standard DIN 3055 , and grant leaving factory.

检验员：

Signature: FANJINHONG

日期

Date: MAY 14, 2015

烟台优佳经贸有限责任公司
ACHBEST COMPANY LTD., YANTAI

ACHBEST COMPANY LTD., YANTAI

RM. 1004 TRIUMPH CENTER, NO. 53 NANSHAN ROAD, YANTAI, CHINA

产品质量证明

CERTIFICATE OF QUALITY

品名

Commodity: E. GALV. WIRE ROPES

结构

Construction 6X7+FC

捻向

Lay Direction RHOL

涂油方式

Lubrication WITHOUT OIL

总数量

Total Quantity 1000M/ REEL

生产标准

Standard : DIN 3055

钢丝绳破断拉力

The least Breaking Strength $\geq 5.96\text{KN}$

公称直径

Nominal Dia 3.0MM

钢丝直径

Wire Dia 0.32MM

公称强度

Nominal Strength $\geq 1770\text{MPA}$

判定：根据以上检验结果，符合产品标准 DIN 3055 要求，准予出厂。

Conclusion: According to the above test result, they accord with the demands of products standard DIN 3055 , and grant leaving factory.

检验员：

Signature: FANJINHONG

日期

Date: MAY 14, 2015

烟台优佳经贸有限责任公司
ACHBEST COMPANY LTD., YANTAI

ACHBEST COMPANY LTD., YANTAI

RM. 1004 TRIUMPH CENTER, NO. 53 NANSHAN ROAD, YANTAI, CHINA

产品质量证明

CERTIFICATE OF QUALITY

品名

Commodity: E. GALV. WIRE ROPES

结构

Construction 6X7+FC

捻向

Lay Direction RHOL

涂油方式

Lubrication WITHOUT OIL

总数量

Total Quantity 1000M/ REELS

生产标准

Standard : DIN 3055

钢丝绳破断拉力

The least Breaking Strength $\geq 10.29\text{KN}$

公称直径

Nominal Dia 4.0MM

钢丝直径

Wire Dia 0.43MM

公称强度

Nominal Strength $\geq 1670\text{MPA}$

判定：根据以上检验结果，符合产品标准 DIN 3055 要求，准予出厂。

Conclusion: According to the above test result, they accord with the demands of products standard DIN 3055 , and grant leaving factory.

检验员：

Signature: FANJINHONG

日期

Date: May 14, 2015

烟台优佳经贸有限责任公司
ACHBEST COMPANY LTD., YANTAI

ACHBEST COMPANY LTD., YANTAI

RM. 1004 TRIUMPH CENTER, NO. 53 NANSHAN ROAD, YANTAI, CHINA

产品质量证明

CERTIFICATE OF QUALITY

品名

Commodity: E. GALV. WIRE ROPES

结构

Construction 6X7+FC

捻向

Lay Direction RHOL

涂油方式

Lubrication WITHOUT OIL

总数量

Total Quantity 1000M/ REEL

生产标准

Standard : DIN 3055

钢丝绳破断拉力

The least Breaking Strength $\geq 16.38\text{KN}$

公称直径

Nominal Dia 5.0MM

钢丝直径

Wire Dia 0.53MM

公称强度

Nominal Strength $\geq 1670\text{MPA}$

判定：根据以上检验结果，符合产品标准 DIN 3055 要求，准予出厂。

Conclusion: According to the above test result, they accord with the demands of products standard DIN 3055 , and grant leaving factory.

检验员：

Signature: FANJINHONG

日期

Date: MAY 14 , 2015

烟台优佳经贸有限责任公司
ACHBEST COMPANY LTD., YANTAI

ACHBEST COMPANY LTD., YANTAI

RM. 1004 TRIUMP CENTER, NO. 53 NANSHAN ROAD, YANTAI, CHINA

产品质量证明

CERTIFICATE OF QUALITY/QUANTITY

品名

Commodity: E. GALV. WIRE ROPES

结构

Construction 6X19+FC

捻向

Lay Direction RHOL

涂油方式

Lubrication LIGHT RUST PROOF OIL

总数量

Total Quantity 500M/ REELS

生产标准

Standard : DIN3060

钢丝绳破断拉力

The least Breaking Strength $\geq 18.45\text{KN}$

公称直径

Nominal Dia 6MM

钢丝直径

Wire Dia 0.37MM

公称强度

Nominal Strength $\geq 1670\text{MPA}$

判定：根据以上检验结果，符合产品标准 DIN3060 要求，准予出厂。

Conclusion: According to the result above test, they accord with the demands of products standard DIN3060, and grant leaving factory.

检验员：

Signature: FANJINHONG

日期

Date: MAY 14, 2015

烟台优佳经贸有限责任公司
ACHBEST COMPANY LTD., YANTAI

ACHBEST COMPANY LTD., YANTAI

RM. 1004 TRIUMP CENTER, NO. 53 NANSHAN ROAD, YANTAI, CHINA

产品质量证明

CERTIFICATE OF QUALITY/QUANTITY

品名

Commodity: E. GALV. WIRE ROPES

结构

Construction 6X19+FC

捻向

Lay Direction RHOL

涂油方式

Lubrication LIGHT RUST PROOF OIL

总数量

Total Quantity 500M/ REELS

生产标准

Standard : DIN3060

钢丝绳破断拉力

The least Breaking Strength $\geq 33.00\text{KN}$

公称直径

Nominal Dia 8MM

钢丝直径

Wire Dia 0.50MM

公称强度

Nominal Strength $\geq 1670\text{MPA}$

判定：根据以上检验结果，符合产品标准 DIN3060 要求，准予出厂。

Conclusion: According to the result above test, they accord with the demands of products standard DIN3060, and grant leaving factory.

检验员：

Signature: FANJINHONG

日期

Date: May 14, 2015

烟台优佳经贸有限责任公司
ACHBEST COMPANY LTD., YANTAI

ACHBEST COMPANY LTD., YANTAI

RM. 1004 TRIUMP CENTER, NO. 53 NANSHAN ROAD, YANTAI, CHINA

产品质量证明

CERTIFICATE OF QUALITY/QUANTITY

品名

Commodity: E. GALV. WIRE ROPES

结构

Construction 6X19+FC

捻向

Lay Direction RHOL

涂油方式

Lubrication LIGHT RUST PROOF OIL

总数量

Total Quantity 1000M/ REEL

生产标准

Standard : DIN3060

钢丝绳破断拉力

The least Breaking Strength $\geq 52.80\text{KN}$

公称直径

Nominal Dia 10MM

钢丝直径

Wire Dia 0.64MM

公称强度

Nominal Strength $\geq 1670\text{MPA}$

判定：根据以上检验结果，符合产品标准 DIN3060 要求，准予出厂。

Conclusion: According to the result above test, they accord with the demands of products standard DIN3060, and grant leaving factory.

检验员：

Signature: FANJINHONG

日期

Date: May 14, 2015

烟台优佳经贸有限责任公司
ACHBEST COMPANY LTD., YANTAI

ACHBEST COMPANY LTD., YANTAI

RM. 1004 TRIUMP CENTER, NO. 53 NANSHAN ROAD, YANTAI, CHINA

产品质量证明

CERTIFICATE OF QUALITY/QUANTITY

品名

Commodity: E. GALV. WIRE ROPES

结构

Construction 6X19+FC

捻向

Lay Direction RHOL

涂油方式

Lubrication LIGHT RUST PROOF OIL

总数量

Total Quantity 250M/ REEL

生产标准

Standard : DIN3060

钢丝绳破断拉力

The least Breaking Strength $\geq 74.00\text{KN}$

公称直径

Nominal Dia 12MM

钢丝直径

Wire Dia 0.76MM

公称强度

Nominal Strength $\geq 1670\text{MPA}$

判定：根据以上检验结果，符合产品标准 DIN3060 要求，准予出厂。

Conclusion: According to the result above test, they accord with the demands of products standard DIN3060, and grant leaving factory.

检验员：

Signature: FANJINHONG

日期

Date: May 14, 2015

烟台优佳经贸有限责任公司
ACHBEST COMPANY LTD., YANTAI

ACHBEST COMPANY LTD., YANTAI

RM. 1004 TRIUMP CENTER, NO. 53 NANSHAN ROAD, YANTAI, CHINA

产品质量证明

CERTIFICATE OF QUALITY/QUANTITY

品名

Commodity: E. GALV. WIRE ROPES

结构

Construction 6X19+FC

捻向

Lay Direction RHOL

涂油方式

Lubrication LIGHT RUST PROOF OIL

总数量

Total Quantity 250M/ REEL

生产标准

Standard : DIN3060

钢丝绳破断拉力

The least Breaking Strength $\geq 102.00\text{KN}$

公称直径

Nominal Dia 14MM

钢丝直径

Wire Dia 0.89MM

公称强度

Nominal Strength $\geq 1670\text{MPA}$

判定：根据以上检验结果，符合产品标准 DIN3060 要求，准予出厂。

Conclusion: According to the result above test, they accord with the demands of products standard DIN3060, and grant leaving factory.

检验员：

Signature: FANJINHONG

日期

Date: May 14, 2015

烟台优佳经贸有限责任公司
ACHBEST COMPANY LTD., YANTAI

ACHBEST COMPANY LTD., YANTAI

RM. 1004 TRIUMP CENTER, NO. 53 NANSHAN ROAD, YANTAI, CHINA

产品质量证明

CERTIFICATE OF QUALITY/QUANTITY

品名

Commodity: E. GALV. WIRE ROPES

结构

Construction 6X19+FC

捻向

Lay Direction RHOL

涂油方式

Lubrication LIGHT RUST PROOF OIL

总数量

Total Quantity 250M/ REEL

生产标准

Standard : DIN3060

钢丝绳破断拉力

The least Breaking Strength $\geq 131.00\text{KN}$

公称直径

Nominal Dia 16MM

钢丝直径

Wire Dia 1.02MM

公称强度

Nominal Strength $\geq 1670\text{MPA}$

判定：根据以上检验结果，符合产品标准 DIN 3060 要求，准予出厂。

Conclusion: According to the result above test, they accord with the demands of products standard DIN 3060, and grant leaving factory.

检验员：

Signature: FANJINHONG

日期

Date: May 14, 2015

烟台优佳经贸有限责任公司
ACHBEST COMPANY LTD., YANTAI