

ACHBEST COMPANY LTD., YANTAI

RM. 1004 TRIUMPH CENTER, NO. 53 NANSHAN ROAD, YANTAI, CHINA

产品质量证明

CERTIFICATE OF QUALITY

品名

Commodity: E. GALV. WIRE ROPES WITH TRANSPARENT PVC COATED

结构

Construction 6X7+FC+PVC

捻向

Lay Direction RHOL

涂油方式

Lubrication WITHOUT OIL

总数量

Total Quantity 250M/ REEL

生产标准

Standard : DIN 3055

钢丝绳破断拉力

The least Breaking Strength $\geq 2.56\text{KN}$

公称直径

Nominal Dia 2-3MM

钢丝直径

Wire Dia 0.21MM

公称强度

Nominal Strength $\geq 1770\text{MPA}$

判定：根据以上检验结果，符合产品标准 DIN 3055 要求，准予出厂。

Conclusion: According to the above test result, they accord with the demands of products standard DIN 3055 , and grant leaving factory.

检验员：

Signature: FANJINHONG

日期

Date: MAY 25, 2015

烟台优佳经贸有限责任公司
ACHBEST COMPANY LTD., YANTAI

ACHBEST COMPANY LTD., YANTAI

RM. 1004 TRIUMPH CENTER, NO. 53 NANSHAN ROAD, YANTAI, CHINA

产品质量证明

CERTIFICATE OF QUALITY

品名

Commodity: E. GALV. WIRE ROPES WITH TRANSPARENT PVC COATED

结构

Construction 6X7+FC+PVC

捻向

Lay Direction RHOL

涂油方式

Lubrication WITHOUT OIL

总数量

Total Quantity 250M/ REEL

生产标准

Standard : DIN 3055

钢丝绳破断拉力

The least Breaking Strength $\geq 2.56\text{KN}$

公称直径

Nominal Dia 2-4MM

钢丝直径

Wire Dia 0.21MM

公称强度

Nominal Strength $\geq 1770\text{MPA}$

判定：根据以上检验结果，符合产品标准 DIN 3055 要求，准予出厂。

Conclusion: According to the above test result, they accord with the demands of products standard DIN 3055 , and grant leaving factory.

检验员：

Signature: FANJINHONG

日期

Date: May 25, 2015

烟台优佳经贸有限责任公司
ACHBEST COMPANY LTD., YANTAI

ACHBEST COMPANY LTD., YANTAI

RM. 1004 TRIUMPH CENTER, NO. 53 NANSHAN ROAD, YANTAI, CHINA

产品质量证明

CERTIFICATE OF QUALITY

品名

Commodity: E. GALV. WIRE ROPES WITH TRANSPARENT PVC COATED

结构

Construction 6X7+FC+PVC

捻向

Lay Direction RHOL

涂油方式

Lubrication WITHOUT OIL

总数量

Total Quantity 250M/REEL

生产标准

Standard : DIN 3055

钢丝绳破断拉力

The least Breaking Strength $\geq 5.96\text{KN}$

公称直径

Nominal Dia 3-5 MM

钢丝直径

Wire Dia 0.32MM

公称强度

Nominal Strength $\geq 1770\text{MPA}$

判定：根据以上检验结果，符合产品标准 DIN 3055 要求，准予出厂。

Conclusion: According to the above test result, they accord with the demands of products standard DIN 3055 , and grant leaving factory.

检验员：

Signature: FANJINHONG

日期

Date: May 25, 2015

烟台优佳经贸有限责任公司
ACHBEST COMPANY LTD., YANTAI

ACHBEST COMPANY LTD., YANTAI

RM. 1004 TRIUMPH CENTER, NO. 53 NANSHAN ROAD, YANTAI, CHINA

产品质量证明

CERTIFICATE OF QUALITY

品名

Commodity: E. GALV. WIRE ROPES WITH TRANSPARENT PVC COATED

结构

Construction 6X7+FC+PVC

捻向

Lay Direction RHOL

涂油方式

Lubrication WITHOUT OIL

总数量

Total Quantity 250M/REEL

生产标准

Standard : DIN 3055

钢丝绳破断拉力

The least Breaking Strength $\geq 10.29\text{KN}$

公称直径

Nominal Dia 4-6 MM

钢丝直径

Wire Dia 0.43MM

公称强度

Nominal Strength $\geq 1670\text{MPA}$

判定：根据以上检验结果，符合产品标准 DIN 3055 要求，准予出厂。

Conclusion: According to the above test result, they accord with the demands of products standard DIN 3055 , and grant leaving factory.

检验员：

Signature: FANJINHONG

日期

Date: May 25, 2015

烟台优佳经贸有限责任公司
ACHBEST COMPANY LTD., YANTAI

ACHBEST COMPANY LTD., YANTAI

RM. 1004 TRIUMPH CENTER, NO. 53 NANSHAN ROAD, YANTAI, CHINA

产品质量证明

CERTIFICATE OF QUALITY

品名

Commodity: E. GALV. WIRE ROPES WITH TRANSPARENT PVC COATED

结构

Construction 6X7+FC+ PVC

捻向

Lay Direction RHOL

涂油方式

Lubrication WITHOUT OIL

总数量

Total Quantity 250M/ 2 REELS

生产标准

Standard : DIN 3055

钢丝绳破断拉力

The least Breaking Strength $\geq 16.38\text{KN}$

公称直径

Nominal Dia 5-7 MM

钢丝直径

Wire Dia 0.53MM

公称强度

Nominal Strength $\geq 1670\text{MPA}$

判定：根据以上检验结果，符合产品标准 DIN 3055 要求，准予出厂。

Conclusion: According to the above test result, they accord with the demands of products standard DIN 3055 , and grant leaving factory.

检验员：

Signature: FANJINHONG

日期

Date: May 25, 2015

烟台优佳经贸有限责任公司
ACHBEST COMPANY LTD., YANTAI

ACHBEST COMPANY LTD., YANTAI

RM. 1004 TRIUMPH CENTER, NO. 53 NANSHAN ROAD, YANTAI, CHINA

产品质量证明

CERTIFICATE OF QUALITY

品名

Commodity: E. GALV. WIRE ROPES WITH TRANSPARENT PVC COATED

结构

Construction 6X7+FC+PVC

捻向

Lay Direction RHOL

涂油方式

Lubrication WITHOUT OIL

总数量

Total Quantity 250M/ 5 REELS

生产标准

Standard : DIN 3055

钢丝绳破断拉力

The least Breaking Strength $\geq 22.50\text{KN}$

公称直径

Nominal Dia 6-8MM

钢丝直径

Wire Dia 0.64MM

公称强度

Nominal Strength $\geq 1670\text{MPA}$

判定：根据以上检验结果，符合产品标准 DIN 3055 要求，准予出厂。

Conclusion: According to the above test result, they accord with the demands of products standard DIN 3055 , and grant leaving factory.

检验员：

Signature: FANJINHONG

日期

Date: May 25, 2015

烟台优佳经贸有限责任公司
ACHBEST COMPANY LTD., YANTAI

ACHBEST COMPANY LTD., YANTAI

RM. 1004 TRIUMPH CENTER, NO. 53 NANSHAN ROAD, YANTAI, CHINA

产品质量证明

CERTIFICATE OF QUALITY

品名

Commodity: E. GALV. WIRE ROPES WITH TRANSPARENT PVC COATED

结构

Construction 6X7+FC+PVC

捻向

Lay Direction RHOL

涂油方式

Lubrication WITHOUT OIL

总数量

Quantity 250M/ REEL

生产标准

Standard : DIN 3055

钢丝绳破断拉力

The least Breaking Strength $\geq 35.4\text{KN}$

公称直径

Nominal Dia 8-10 MM

钢丝直径

Wire Dia 0.85MM

公称强度

Nominal Strength $\geq 1670\text{MPA}$

判定：根据以上检验结果，符合产品标准 DIN 3055 要求，准予出厂。

Conclusion: According to the above test result, they accord with the demands of products standard DIN 3055 , and grant leaving factory.

检验员：

Signature: FANJINHONG

日期

Date: MAY 25 , 2015

烟台优佳经贸有限责任公司
ACHBEST COMPANY LTD., YANTAI

ACHBEST COMPANY LTD., YANTAI

RM. 1004 TRIUMPH CENTER, NO. 53 NANSHAN ROAD, YANTAI, CHINA

产品质量证明

CERTIFICATE OF QUALITY

品名

Commodity: E. GALV. WIRE ROPES WITH TRANSPARENT PVC COATED

结构

Construction 6X7+FC+PVC

捻向

Lay Direction RHOL

涂油方式

Lubrication WITHOUT OIL

总数量

Quantity 250M/ REEL

生产标准

Standard : DIN 3055

钢丝绳破断拉力

The least Breaking Strength $\geq 55.50\text{KN}$

公称直径

Nominal Dia 10-12MM

钢丝直径

Wire Dia 1.06MM

公称强度

Nominal Strength $\geq 1670\text{MPA}$

判定：根据以上检验结果，符合产品标准 DIN 3055 要求，准予出厂。

Conclusion: According to the above test result, they accord with the demands of products standard DIN 3055 , and grant leaving factory.

检验员：

Signature: FANJINHONG

日期

Date: May 25, 2015

烟台优佳经贸有限责任公司
ACHBEST COMPANY LTD., YANTAI